


Surgical and Isolation Masks



- These masks adhere to ASTM F2100-11, the recognized standard for medical face masks
- ASTM Level 1 protection is ideal for average fluid exposure procedures; ASTM Level 2 protection is ideal for moderate fluid exposure procedures; ASTM Level 3 protection is ideal for high fluid exposure procedures
- Optimal breathability for longer procedures
- Ultrasonically welded seams for added protection
- 16 CFR Part 1610: Class I Flammability
- Not made with natural rubber latex

DESCRIPTION	COLOR	REORDER NUMBER	PACKAGING
ASTM Level 1			
Earloop Procedure Mask	Blue	2453	50/bx; 6 bxs/cs
Earloop Procedure Mask	Yellow	2454	50/bx; 6 bxs/cs
Surgical Tie Mask	Light Blue	2460	50/bx; 6 bxs/cs
Surgical Tie Mask, Horizontal Ties	Gray	2461	50/bx; 6 bxs/cs
Surgical Tie Mask, Soft Bill	Light Blue	2462	50/bx; 6 bxs/cs
Surgical Tie Mask, Large Soft Bill	Green	2463	50/bx; 6 bxs/cs
Surgical Tie Mask with Anti-Fog Foam	Denim Blue	2464	50/bx; 6 bxs/cs
Surgical Tie Mask with Anti-Fog Film	Green	2465	50/bx; 6 bxs/cs
Surgical Tie Mask with Anti-Fog Tape	Green	2466	50/bx; 6 bxs/cs
Surgical Tie Mask, Soft Lining	White	2470	50/bx; 6 bxs/cs
Surgical Tie Mask with Anti-Fog Foam, Soft Lining	White	2472	50/bx; 6 bxs/cs

ASTM F2100 TESTING

TEST & STANDARD	ASTM 1	ASTM 2	ASTM 3
Bacterial Filtration Efficiency (BFE) at 3.0 micron (ASTM F2101)	≥ 95%	≥ 98%	≥ 98%
Particulate Filtration Efficiency (PFE) at 0.1 micron (ASTM F2299)	≥ 95%	≥ 98%	≥ 98%
Synthetic Blood Penetration Resistance, mmHg (ASTM 1862)	80	120	160
Differential Pressure (ΔP), mm H ₂ O/cm ² (MIL-M-36954C)	< 5.0	< 6.0	< 6.0
Flammability Rating (16 CFR part 1610)	Class 1		

MRI Safe Earloop Masks



- Safe for use during MRI procedures
- Complies with FDA safety recommendations
- ASTM Rated Level 2 for moderate fluid exposure
- Soft breathable material; plastic nose bar
- 16 CFR Part 1610: Class I Flammability
- CA Prop 65 compliant
- Not made with natural rubber latex

DESCRIPTION	COLOR	REORDER NUMBER	PACKAGING
MRI Safe Earloop Mask	Blue	2497	50/bx; 6 bxs/cs

Protective Eye Wear



- Lightweight and disposable
- Safety Glasses are UV protective and feature side vents
- Not made with natural rubber latex

DESCRIPTION	COLOR	REORDER NUMBER	PACKAGING
Safety Glasses	Clear	2489	12/bx; 25 bxs/cs